

Dancestep® Plus

BLACK 11051000

GREY 11052000

PRODUCT DESCRIPTION

Dancestep® Plus is a foam-backed flooring intended to be placed directly on top of concrete as well as textured or embossed Marley flooring, designed to be non-slip and an ideal surface for contemporary, jazz and all dance forms requiring superior non-slip. This flooring is not suitable for tap or excessive pointe work. A fiberglass lining improves stability and offers better lie-flat. Flexible for easy roll-out and roll-up like a standard Marley. Resists wear and tear. **Dancestep Plus** does not require a floating wood subfloor.

SIZE & PACKAGING

Width:	6.56 FT (2 M)
Full Roll Length:	65 FT (20 M)
Thickness:	.24 IN (6.0 MM)
Wear Layer:	.03 IN (0.7 MM)
Weight:	6.73 LBS/SY (3.65 KG/SM)
Total Roll Weight:	322 LBS (146 KG)

INSTALLATION

Dancestep Plus is to be unrolled or unraveled so that the exterior surface (dance surfaces) faces up. Never attempt to flip the flooring over.

When using semi-permanently or permanently on concrete or cement floor, use a liquid vapor barrier such as **Bone Dry Plus** to seal the slab. Follow directions accordingly, but typically when a porous floor absorbs **Bone Dry Plus** within a 15-minute period, recoating is required.

All vinyl flooring must be acclimated for a period of 24 hours at the temperature which will be maintained for the life of the flooring and lie flat prior to installation. Reliance of adhesion to flatten flooring is inadvisable.

Flooring may be loose laid with top tape on the seams and along the perimeter, semi-permanently installed with double-faced tape or **ReUselt®** with optional top tape depending on the techniques employed, or permanently adhered with a full-spread glue. When using double-faced tape, different practices may apply. 4" double-faced tape can be used lengthwise: 1) 3 lengths, down the middle and along the perimeter on the left and right side; 2) 2 strips, along the perimeter on the left and right side, or 3) the left side or the right side, and panel sharing when abutting an adjacent roll. One or two strips of double-faced tape will also be taped spanning the width at the end of the length. When using glue, **Dancestep Plus** should be installed with a pressure-sensitive adhesive using a "semi-dry" application.

Stagestep, 4701 Bath St, Bldg 46B, Philadelphia, PA 19137



a company of **Gerflor**

INSTALLATION (continued)

Seam welding is not recommended. All seam welding should be done only by a professional.

Always clean newly installed Marley or vinyl flooring. See weekly maintenance directions below.

CLEANING

Broom sweep or vacuum daily to remove coarse dirt, dust and debris.

Spot clean when necessary to remove scuffs or caustic spills or residue.

Mop clean weekly or as required with **ProClean®**, a neutral detergent-degreaser using the two-bucket method. One bucket is for the **ProClean** (2 oz **ProClean** to a gallon of water). The second bucket is for clear water to rinse the mop. Mop dry. Although **ProClean** is a non-rinse product, it is always preferable to rinse and remove excess moisture with a towel or clean dry mop.

Do not use alcohol, ammonia, acetone, bleach, cleansers, vinegar, or solvents to clean surface. Exposure to sunlight can cause reduced life expectancy due to UV radiation. Change in temperature and humidity can negatively affect installation and non-slip characteristics.

HANDLING & STORAGE

Handling: Normal safe handling practices must be applied.

Always use a suitable core tube which is no less than the full width of the rolls and has an interior diameter of 4 inches or greater.

It is recommended that rolls are stored in the vertical position and restrained in position using safety chains or straps. If the flooring is moved in a horizontal position, do not rest flat surfaces above, and return to vertical position immediately after transit. Prolonged horizontal positioning may result in roll-set whereby the rolled material takes on an oval shaped, causing stretch marks and irreversible damage.

Stagestep, 4701 Bath St, Bldg 46B, Philadelphia, PA 19137



a company of **Gerflor**

PHYSICAL PROPERTIES/TESTING

PROPERTIES	STANDARD	RESULT
Total thickness	EN ISO 24346	6.0 mm (+.08/- .15)
Wear Layer Thickness	EN ISO 24340	.7 mm (+10%/- 13%)
Wear Layer Density	EN ISO 23996	1250 kg/mm ³ (+/- 50)
Foam Layer Thickness	EN ISO 24340	4.8 mm
Length of Roll	EN ISO 24341	20 m (65 ft)
Width	EN ISO 24341	2 m (6.56 ft)
Total Weight	EN ISO 23997	3.65 kg/m ²
Dimensional Stability	EN ISO 23999	0.2 max. %
Curling	EN ISO 23999	8 max. mm
Hot Weld Strength	EN 684	>240 (N/60 mm)
Abrasion Group	EN 660-2	T
Light Fastness	EN ISO 105-B02	>6 Grade
Fire Resistance	EN 13501-1	Class Cfl-s1
Critical Radiant Flux	ASTM E648	Class 1 – Meets or Exceeds
Smoke Density (Non-Flaming)	ASTM E662	<450 DMC - Meets
Resistance to Indentation	EN 1516	0.5 min mm
Chemical Resistance	EN ISO 26987	High Resistance
Slip Resistance	EN 13893	Class DS
Castor Chair Resistance	EN 425	Slight Change
Furniture Leg	EN 424	No Damage

Stagestep, 4701 Bath St, Bldg 46B, Philadelphia, PA 19137



a company of **Gerflor**