

TIMESTEP®
SOLID BLACK - 11011000
SOLID GREY - 11012000
MARBLEIZED GREY - 11013000
MARBLEIZED TAN - 11014000

PRODUCT DESCRIPTION

Timestep roll-out dance flooring is the ultimate multi-purpose floor ideally suited for all movement activity including tap, hip-hop, ballet, modern, character, ballroom, jazz and flamenco. Made of 2mm (.08") thick solid homogeneous PVC. Heavy-duty flooring for stage, touring and studio. Can handle heavy scenery and props. Surface can be treated for differing degrees of non-slip.

SIZE & PACKAGING

Width:	6.56 FT (2 M)
Full Roll Length:	65 FT (20 M)
Thickness:	.08 IN (2 MM)
Wear Layer:	.08 IN (2 MM)
Weight:	5.9 LBS/SY (3.2 KG/SM)
Total Roll Weight:	282 LBS (128 KG)

INSTALLATION

Timestep is to be unrolled or unraveled so that the exterior surface (dance surfaces) faces up. Never attempt to flip the flooring over.

All vinyl flooring must be acclimated and lie flat prior to installation. Reliance of adhesion to flatten flooring is inadvisable.

Flooring may be loose laid with top tape on the seams and along the perimeter, semi-permanently installed with double-faced tape or **ReUseIt®** with optional top tape depending on the techniques employed, or permanently adhered with a full-spread glue. Timestep should be installed with an adhesive using a "semi-wet" application.

Always clean newly installed Marley or vinyl flooring. See weekly maintenance directions below.

Seam welding is not recommended.

CLEANING

Broom sweep or vacuum daily to remove coarse dirt, dust and debris.

Spot clean when necessary to remove scuffs or caustic spills or residue.

Mop clean weekly or as required with **ProClean®**, a neutral detergent-degreaser using the two-bucket method. One bucket is for the **ProClean** (2 oz **ProClean** to a gallon of water). The second bucket is for clear water to rinse the mop. Use of a microfiber mophead is preferable especially for tap shoe residue.

Do not use alcohol, ammonia, acetone, bleach, or solvents to clean surface. Exposure to sunlight can cause reduced

Stagestep, 4701 Bath St, Bldg 46B, Philadelphia, PA 19137



a company of **Gerflor**

CLEANING (continued)

life expectancy due to UV radiation. Change in temperature and humidity can negatively affect installation and non-slip characteristics.

HANDLING & STORAGE

Handling: Normal safe handling practices must be applied.

Always use a suitable core tube which is no less than the full width of the rolls and has an interior diameter of 4 inches or greater.

It is recommended that rolls are stored in the vertical position and restrained in position using safety chains or straps. If the flooring is moved in a horizontal position, do not rest flat surfaces above, and return to vertical position immediately after transit. Prolonged horizontal positioning may result in roll-set whereby the rolled material takes on an oval shaped, causing stretch marks and irreversible damage.

PHYSICAL PROPERTIES/TESTING

PROPERTIES	STANDARD	RESULT
Thickness	ISO 24346 (EN 428)	2.0mm
Roll Size	ISO 24341 (EN 426)	2m x 20m = 40m ²
Total Weight	ISO 23997 (EN 430)	3200/m ²
General Performance	ISO 10582 (EN 649)	Conforms
	ASTM F1913	Conforms
	ASTM F1700	Class 1, Type A
Use Area	ISO 10874 (EN 685)	Home, School, Factory
Reaction to Fire	EN 13501-1	Class Bfl-S1
	ASTM E662	<450
	ASTM E648	Class 1
	CAN/ULC S102.2	FSV < 300; SDV < 500
	AS ISO 9239-1	SCOF ≥0.6
Abrasion Resistance	EN 649	Group M
Binder Content	ISO 10582	Type II
Slip Resistance	EN 13893	Class DS
	AS 4586	R9
	ASTM D2047	SCOF ≥0.5
	DIN 51130 / DIN EN 16165 Ann. B	R9
	DIN 51130 / DIN EN 16165 Ann. B	R10
Residual Indentation	ISO 24343-1 (EN 433)	≤0.10mm
	ASTM F970 (Modified)	< 0.005" (750 psi)
Impact Sound Reduction	ISO 10140-3	4d
Static Electrical Propensity	EN 1815	2.0kV Classified as 'antistatic
Resistance to Chemicals	ISO 26987 (EN 423)	Good
Light Fastness	ISO 105-B02 (Method 3)	≥6
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
VOC Emissions	Indoor Air Comfort GOLD	Eurofins certified product
	AgBB/ABG	Pass
	FloorScore	Certified
	Finnish M1	Certified